

OpenText Axcelerate 5.13.1

Default Fields in Axcelerate Review & Analysis

This color = change introduced with Axcelerate 5.13.1							
This color = new field introduced with Axcelerate 5.13.1		Table is sorted by display names		Searchable		Results list	
Internal field name	Display name used for Results list column, Smart Filter, Metadata fly-in etc.	Description	If field content matches global search query (and without the use of field based search), this has an influence on the search result.	If field content matches the query, terms are highlighted	Field can be searched with the Search in Smart Filter	Displayable in Axcelerate 5 Results list	Sortable in Axcelerate 5 Results list
ax_reviewers	-	Tracks all reviewers known to the system; used to map from the user id to the display name. Used, e.g., for batch assignment and user specific access to review states.					
Conversation	-	The field contains a complete XML representation of a chat conversation.	√				
meta_rfc5322_thread_path	-	Used for thread detection by header analysis for RFC 5322 compliant emails. Contains IDs of all parent emails and the current email.					
meta_rfc5322_thread_root	-	Used for thread detection by header analysis. Contains ID of the email to which the current email replies.					
rm_filesize	-	Size of the item in bytes. Depending on the item type, this value might not be exact and only estimated for certain file types. Value is used as a fallback option for the virtual_filesize field.					
rm_footer	-	Content of the footer as detected by the CORE footer detection mechanisms (when enabled).	√				
rm_native_filename	-	Path to the native file in its original location					
ax_cust_multi_<letter>	(Custom Multivalue <number>) Custom field name is given in Axcelerate 5 UI	Custom multivalue field for use in Axcelerate 5				√	
ax_cust_hrchy_<letter>	(Custom Hierarchy <number>) Custom field name is given in Axcelerate 5 UI	Custom hierarchical field for use in Axcelerate 5				√	
ax_cust_single_<letter>	(Custom Single Value <number>) Custom field name is given in Axcelerate 5 UI	Custom single value field for use in Axcelerate 5				√	
ax_cust_text_<letter>	(Custom Text <number>) Custom field name is given in Axcelerate 5 UI	Custom text field for use in Axcelerate 5			√		
meta_recipient	All Recipients	Email - To, CC or BCC email address (includes email address and display name), or chat message recipient address	√	√		√	

This color = change
introduced with Axcelerate 5.13.1

This color = new field introduced with
Axcelerate 5.13.1

Internal field name	Available	How and where the field is filled				Remarks
		Before publish	Before publish, details	User input/tagging/fielding	Axcelerate 5 feature	
ax_reviewers						
Conversation		v				
meta_rfc5322_thread_path			Information gathered during indexing		Publish The information gathered during indexing is filled into the field during the publish.	Requires that data is ingested with Axcelerate 5.2 or higher.
meta_rfc5322_thread_root			Information gathered during indexing		Publish The information gathered during indexing is filled into the field during the publish.	Requires that data is ingested with Axcelerate 5.2 or higher.
rm_filesize		v				
rm_footer		v				
rm_native_filename					Publish	
ax_cust_multi_<letter>				v		
ax_cust_hrchy_<letter>				v		
ax_cust_single_<letter>				v		
ax_cust_text_<letter>				v		
meta_recipient	v	v				

This color = change introduced with Axcelerate 5.13.1

This color = new field introduced with Axcelerate 5.13.1

Table is sorted by display names			Searchable			Results list	
rm_attachmentroot	Attachment Family ID	Field to group and sort parent/attachments together - NOTE: The document in the group without a Parent ID is the parent document.					
att_p	Attachment Text	Text of an attachment.	√	√	√		
attachment	Attachments Names	Names of attachments	√	√	√		
rm_childlink	Attachments/Embeddings	URI to access the original attachment/embedding					
ax_batch	Batch	Names of batches created for review				√	
rm_bates	Bates	Bates numbers of Axcelerate productions	√	√	√	√	
begbates	BEGBATES	Begbates of external productions		√			
rm_messagecount	Chat Count	Number of messages in a chat					
rm_chatevent	Chat Event Type	Type of event within a chat, such as: - Attachment Sent - Chat Message - Confidential Message Sent - History Viewed - Invite With Message Sent - Person Entering - Person Leaving					
model-70	Concept Groups	Concept Groups, only created if learning was enabled for publishing. Prerequisite to Concept Browser.	√	√		√	
rmConversion	Conversion	Conversion status of the document as shown in the Redaction view				√	
rm_creationdate	Creation Date	Creation date of a document				√	√
rm_custodian	Custodian	Custodian of the file entered at crawl time	√	√		√	√
rm_cust_association	Custom Association	Values for custom associations		√			
rm_source	Data Source Name	Data source name				√	
rm_deliverydate	Date Received	Depending on the email program, the delivery date means the date when the email was received, delivered or last stored.				√	√

This color = change
introduced with Axcelerate 5.13.1

This color = new field introduced with
Axcelerate 5.13.1

	Available	How and where the field is filled				Remarks
rm_attachmentroot	√	√				
att_p	√	√	Automatic population during indexing			
attachment	√	√				
rm_childlink		√				
ax_batch	√				Batch creation	
rm_bates	√				Production	Bates numbers created during production use a specific format. This makes the Bates field behave differently from other fields: Although the Bates field is configured as searchable, you can only search for Bates numbers with the Bates Smart Filter and field based search.
begbates					Can be filled with CSV load before publish or CSV merge after publish	Bates numbers are treated differently from other fields. This explains why the field can contain multiple values, without being configured as "Multi Value" in the document model.
rm_messagecount	√	√			Bloomberg files	
rm_chatevent	√	√			Bloomberg files	
model-70	√				Learning during publish	
rmConversion	√				Conversion, CSV merge with images, CSV load with images (in Axcelerate Ingestion)	
rm_creationdate	√	√				
rm_custodian	√	√				
rm_cust_association			CSV load possible		CSV merge or manageTaxonomy script	
rm_source	√	√				
rm_deliverydate	√	√				

This color = change
introduced with Axcelerate 5.13.1

This color = new field introduced with
Axcelerate 5.13.1

Table is sorted by display names			Searchable			Results list	
meta_documentcharacteristics	Document Characteristics	Characteristic document properties that are of interest such as: - With Natives - Without Natives - With Embeddings (Document is an MS Office document or an email containing comments or sub documents) - Without Embeddings - With Text - Without Text - No Delivered-To - Without Text (e.g. Zip archive, calendar entry, email without body, image file) - With Attachments (for Emails) - Without Attachments (for Emails) - Text extracted by OCR - OCR extraction failed - Chat content				v	
meta_docdate	Document Date	Document Date is a hybrid field. It takes one date, following this default priority: - rm_sentdate (Emails or Attachments) - rm_deliverydate (Emails or Attachments) - rm_lastmodifieddate (Standard files) - rm_creationdate				v	v
meta_title	Document Title	Subject for Emails; Microsoft Office documents: "Title" contents if it exists; otherwise the file name	v	v	v	v	v

This color = change introduced with Axcelerate 5.13.1							
This color = new field introduced with Axcelerate 5.13.1		Available	How and where the field is filled				Remarks
meta_documentcharacteristics	√	√					
meta_docdate	√	√					
meta_title	√	√					

This color = change
introduced with Axcelerate 5.13.1

This color = new field introduced with
Axcelerate 5.13.1

Table is sorted by display names			Searchable			Results list	
rm_doctype	Document Type	Types of documents as defined by Axcelerate eDiscovery. Possible values: - eMail - eMail with attachment - eMail without attachment - Calendar entry - Calendar entry with attachment - Calendar entry without attachment - Archive - Pst - NSF - Standard file - Standard file without attachment - Standard file with attachment - Unspecified - Directory - Contact - Contact with attachment - Contact without attachment - Task - Task with attachment - Task without attachment - Note - Note with attachment - Note without attachment - Post - Post with attachment - Post without attachment - Activity - Activity with attachment - Activity without attachment - E-Mail Stub - Privileged Communication - Miscellaneous - Attachment (attachment of something) - Embedding (embedding of something) - Bookmark (Box bookmarks)				v	
meta_fromdomain	Domain From	Email - from domain (extracted from email address)	v			v	
meta_recipientdomain	Domain To/CC/BCC	Email - recipient domain (extracted from email address)	v			v	
meta_bcc	Email BCC	Email - Bcc email address (includes email address and display name)	v	v	v	v	
meta_cc	Email CC	Email - cc email address (includes email address and display name)	v	v	v	v	
endbates	ENDBATES	Endbates of an external production.		v			
rmerror	Exception	Detailed error description				v	
rmerrorclass	Exception Class	Exception classes give an orientation of where the exception occurred.				v	v
rmerrortype	Exception Type	There can be different exception types in one exception class. Exception types provide additional information.				v	v
rm_external_identifier	External Bates	Field allows to search Bates ranges for external Bates numbers and produce with external Bates numbers.		v		v	

This color = change introduced with Axcelerate 5.13.1						
This color = new field introduced with Axcelerate 5.13.1						
	Available	How and where the field is filled				Remarks
rm_doctype	√	√				
meta_fromdomain	√	√				
meta_recipientdomain	√	√				
meta_bcc	√	√				
meta_cc	√	√				
endbates					Can be filled with CSV load before publish or CSV merge after publish	Bates numbers are treated differently from other fields. This explains why the field can contain multiple values, without being configured as "Multi Value" in the document model.
rmerror	√	√				
rmerrorclass	√	√				
rmerrortype	√	√				
rm_external_identifier		√			Can be filled with CSV load before publish or CSV merge after publish	

This color = change introduced with Axcelerate 5.13.1

This color = new field introduced with Axcelerate 5.13.1

Table is sorted by display names			Searchable			Results list	
rm_external_identifier_pni_prefix	External Bates Prefix	Field allows to search Bates ranges for external Bates numbers and produce with external Bates numbers.					
rm_fileextension	File Extension	File extension as detected and delivered by the connector				√	
fileformat	File Format	Legacy field. Not used in current version					
rm_filename	File Name	Names of standard files.	√	√	√		
virtual_filesize	File Size	Size of the item. If native file for the item was not copied, information is taken from the rm_filesize field. For items with a native copy, the size of that copy is used.				√	
meta_filesizetype	File Size Type	File size range: - </= 200,000 Bytes - >200,000, </=2,000,000 Bytes - >2,000,000 and </=5,000,000 Bytes - > 5,000,000 Bytes				√	
rm_foldername	Folder Name	Email program or PST folder containing the email	√	√		√	
rm_numeric_identifier	ID	Unique identifier for the item in and across ECA/R&A. Is used as merge key .	√	√	√	√	√
rm_image_md5	Image MD5 Hash	Checksum for images imported via CSV Load or CSV Merge, to be used for consistency checks.					
rm_importanceflag	Importance	Importance of an email, as defined by the sender				√	
ax_issue	Issues	Multivalue field used for tagging. Values are added depending on matter.				√	
rmJobStatus	Job Processing	Bulk jobs with date of execution. This allows users to find documents processed by specific jobs. Exceptions are marked, too.					
rm_document_language	Language	Language of a document as found by the language detection (as e.g. specified in the lang attribute in the header of a HTML document).				√	
rm_loadbatch	Load Batch Name	Name of load batch as defined for data loading to Axcelerate Ingestion.				√	
rm_location	Location	File system path or Internet URL, either to the loose file, or to the container the document belongs to (e.g. a PST archive).			√	√	
rm_md5	MD5 Hash	Checksum of the native file.			√		

This color = change
introduced with Axcelerate 5.13.1

This color = new field introduced with
Axcelerate 5.13.1

	Available	How and where the field is filled				Remarks
rm_external_identifier_pni_prefix		✓			Is filled automatically when the External Bates field is filled.	
rm_fileextension	✓	✓				
fileformat		✓				
rm_filename	✓	✓				
virtual_filesize	✓	✓				
meta_filesizetype	✓	✓				
rm_foldername	✓	✓				
rm_numeric_identifier	✓	✓				
rm_image_md5	✓	✓			Can also be filled after publish, through CSV Merge.	
rm_importanceflag	✓	✓				
ax_issue	✓			✓		
rmJobStatus	✓			✓	Filled when bulk jobs are executed: Conversion, global redaction, redaction removal, production, print, OCR	
rm_document_language	✓	✓				
rm_loadbatch	✓	✓				
rm_location	✓	✓				
rm_md5	✓	✓			When files are stored via CSV Merge, MD5 hash can be filled in, too.	

This color = change introduced with Axcelerate 5.13.1										
This color = new field introduced with Axcelerate 5.13.1			Table is sorted by display names			Searchable			Results list	
rm_mimetype	Mime Type	The file type as it is extracted from the properties of the file, as opposed to the file extension.				√	√			
rm_lastmodifieddate	Modification Date	Date showing when a specific document was last modified				√	√			
rm_copy_location	Native Location	Field used internally, by certain native copy modes.								
ax_nr_term_hit_types	Non-Relevant Hit Types	Groups of non-relevant hits								
ax_nr_term_hits	Non-Relevant Hits	User-defined keywords that are characteristic for non-relevant documents								
form	NSF Form	Types of Lotus Notes documents (e.g. message, reply).				√				
rm_attachmentcount	Number of Attachments	Number of attachments								
rm_embedding count	Number of Embeddings	Number of embeddings								
office_flags	Office Flags	Extracts and flags Microsoft Office file properties such as, footers, hidden slides, track changes, etc.				√				
rmNumberImagePages	Pages	Number of image pages available for a document				√				
rm_parentlink	Parent ID	Link to the parent document in internal key format.								
ax_restricted	Apply Custom Security to Document	Helps to set custom security for viewer features via the Axcelerate 5 frontend. Possible values: - Restrict Download - Restrict Image View - Restrict Near Native View - Restrict Redaction View				√				
phrase	Phrases	Phrases as detected by the automatic phrase detection.				√				
ax_privilege	Privilege	Tagging field used to mark privilege information. Default values can be renamed, new values can be added.				√				
ax_privilege_search_types	Privilege Hit Types	Groups of privilege hits								
ax_privilege_search	Privilege Hits	User-defined keywords that are characteristic for privilege documents								
rmProductionSummary	Production	Production names								
ax_production_workflow	Production Workflows	Used for adding documents to production workflows, and for production management.				√				
rm_saved_search	Published Terms	Name of the saved search used to add the document to a matter.								
meta_read	Read/Unread	Email read - yes or no				√				
meta_to	Recipient Address	Email recipient address (includes email address and display name) or chat message recipient address	√	√	√	√				
rm_recipientcount	Recipient Count	Number of recipients in an email or chat								

This color = change
introduced with Axcelerate 5.13.1

This color = new field introduced with
Axcelerate 5.13.1

	Available	How and where the field is filled				Remarks
rm_mimetype	√	√				
rm_lastmodifieddate	√	√				
rm_copy_location	√	√				
ax_nr_term_hit_types	√				Smart Tagger	
ax_nr_term_hits	√				Smart Tagger	
form	√	√				
rm_attachmentcount	√	√				
rm_embedding count	√	√				
office_flags	√	√				
rmNumberImagePages	√	√	Automatic population during indexing, CSV merge, CSV load possible		Conversion or CSV Merge	
rm_parentlink	√	√				
ax_restricted				√	Custom security settings to restrict display and download of specific documents in the viewer	
phrase	√				Publish	
ax_privilege	√			√		
ax_privilege_search_types	√				Smart Tagger	
ax_privilege_search	√				Smart Tagger	
rmProductionSummary					Production	
ax_production_workflow				√	Production	
rm_saved_search	√	√				
meta_read	√	√				
meta_to	√	√				
rm_recipientcount	√	√				

This color = change introduced with Axcelerate 5.13.1							
This color = new field introduced with Axcelerate 5.13.1	Table is sorted by display names		Searchable			Results list	
meta_recipientname	Recipient Name	Email - recipient name (extracted from email address)	√	√		√	
rmRedaction	Redaction	Whether document was redacted or requires redaction				√	
rmRedactColor	Redaction Color	Color of the redaction applied in the viewer.				√	
rm_redaction_labels	Redaction Labels	Legacy field used in Axcelerate Analysis/Axcelerate Review for searchable redaction labels			√		
redaction_reason	Redaction Notes	Reason document was redacted as commented by reviewer.			√		
rmRedactReason	Redaction Reason	Redaction reason that can be added in the viewer.				√	
ax_responsiveness	Responsiveness	Single value field used to tag documents as Responsive or Not responsive. Default values can be renamed and new values can be added.				√	
ax_responsive_term_types	Responsive Term Types	Groups of responsive hits					
ax_responsive_terms	Responsive Terms	User-defined keywords that are characteristic for responsive or relevant documents					
ax_message	Review Comment	Text field for reviewer comments, filled in during review.			√		
ax_reviewed_by	Reviewed by	Name of user who tagged the document using a tagging arrangement.				√	
ax_review_state	Review State	Status of review. Review states can be customized.				√	
ax_pc_workflow	Review Workflows	Names of universes, review workflows, sets, iterations, samples				√	
meta_from	Sender Address	Email sender address (includes email address and display name) or chat message sender address	√	√	√	√	√
meta_fromname	Sender Name	Email sender name (extracted from email address) or chat message sender name	√	√		√	
meta_fromauthor	Sender/Author	Sender of an email or chat message, or author of a document	√	√	√	√	
rm_sentdate	Sent Date	Date showing when a specific email was sent				√	√
rmstoragetype	Storage Type	Describes how a file is stored. Possible values: - File - Attachment - Archive entry - Box entry - Embedding - Web - Database entry - PST entry - OpenText entry - Sharepoint entry - Unspecified				√	

This color = change
introduced with Axcelerate 5.13.1

This color = new field introduced with Axcelerate 5.13.1	Available	How and where the field is filled				Remarks
meta_recipientname	√	√				
rmRedaction	√			√	Redaction	
rmRedactColor					Redaction	
rm_redaction_labels						
redaction_reason	√			√		
rmRedactReason					Redaction	
ax_responsiveness	√			√		
ax_responsive_term_types	√				Smart Tagger	
ax_responsive_terms	√				Smart Tagger	
ax_message	√			√		
ax_reviewed_by	√				Review	
ax_review_state	√			√	Review	The tagging arrangement decides whether the review state is added automatically to a document, or by the user.
ax_pc_workflow				√	Universes and review workflows	
meta_from	√	√				
meta_fromname	√	√				
meta_fromauthor	√	√				
rm_sentdate	√	√				
rmstoragetype	√	√				

This color = change
introduced with Axcelerate 5.13.1

This color = new field introduced with
Axcelerate 5.13.1

Table is sorted by display names

Searchable

Results list

rm_storename	Store Name	Name of the storage container an item is a member of. (E.g the PST for Outlook items extracted from that file)	√	√		√	
rm_subject	Subject	Email subject	√	√	√		
rmProduction	Sub-Production	Production names, sub-production names, production status					
TEMPLATE_AdvancedSearchField	TEMPLATE_AdvancedSearchField	Template field, available to clone from					
TEMPLATE_date	TEMPLATE_date	Template field, available to clone from					
TEMPLATE_PreviewField	TEMPLATE_PreviewField	Template field, available to clone from					
TEMPLATE_Smartfilter	TEMPLATE_Smartfilter	Template field, available to clone from					
TEMPLATE_TaggingField	TEMPLATE_TaggingField	Template field, available to clone from					
p	Text	Paragraph like content spanning one or more <text> elements and other subtags	√	√	√		
uri	URI	Path to element - For certain email types this includes the message ID of the item. For attachments, attachment information is added.			√	√	
rm_view_conversion	View Conversion	Field for internal use: Conversion status by view, as tracked internally by the viewer. Relevant conversion status is tracked in the Conversion field.				√	
ax_workspace	Workspace	This is a customizable hierarchical field that can be used for foldering.				√	

This color = change
introduced with Axcelerate 5.13.1

This color = new field introduced with
Axcelerate 5.13.1

	Available	How and where the field is filled				Remarks
rm_storename	√	√				
rm_subject	√	√				
rmProduction	√				Production	
TEMPLATE_AdvancedSearchField						
TEMPLATE_date						
TEMPLATE_PreviewField						
TEMPLATE_Smartfilter						
TEMPLATE_TaggingField						
p	√	√				
uri	√	√				
rm_view_conversion					Conversion, CSV load with images, CSV merge with images	
ax_workspace	√			√		